

HIGHLIGHTS

- EXCEPTIONAL EXPERIENCE
- INTUITIVE AND EASY TO USE
- 1.4 MP HD 960P
- POE (OPTIONAL)
- DAY NIGHT 30 MTR IR
- PRIVACY MASKING
- ALL IN ONE SOLUTION

MOUNTXROSS MXDV1430S



THE INDOOR MOUNTXROSS CAMERAS ARE EASY-TO-INSTALL AND ARE SUITABLE FOR SURVEILLANCE APPLICATIONS IN AREAS SUCH AS HOMES , CLASSROOM, COLLEGES , RESTAURANTS , HOTELS , MARKETS ETC.

HIGH IMAGE QUALITY IS MAINTAINED EVEN IN LOW LIGHT CONDITIONS, THANKS TO THE MOUNTXROSS CAMERAS DAY/NIGHT FUNCTIONALITY. SUPPORT FOR WIDE DYNAMIC RANGE ENABLES OBJECTS IN BOTH DARK AND LIGHT AREAS OF A SCENE TO BE VISIBLE .THE INDOOR MOUNTXROSS MXDV1430S CAN OPERATE IN TEMPERATURES FROM -10 °C TO 50 °C .



CAMERA

Image Sensor	1/3" 1.4MP High-resolution CMOS Sensor
Main processor	1.400MHz with H.264 encoding
Resolution	960P
Effective pixels	1280(H)*960(V)
Main Stream	1280*960 & 1280x720@25fps
Usable Illumination	0.01 Lux
Electronic shutter time	Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec
S/N ratio	≥50dB
Scanning system	Progressive
Video output	Network

LENS

Focus Length	2.8-12mm
Focus Control	Manual
Lens Type	Manual
Pixels	2M Pixels

CAMERA FEATURES

Day/Night	Color/ B&W (IR-CUT)
Compression	H.264/JPEG/AVI
Image Config	Saturation/Brightness/Contrast / Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)
Back Light Compensation	YES
WDR	YES
Low Bandwidth Consumption	NO
Denoise	YES
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/NAS/CMS/Web
Language	English, French, Japanese, Russian, Korean, Chinese, Turkish, Spanish, Bulgarian, German, Farsi, Polish, Portuguese, Italian, Hebrew

NIGHT VISION

Infrared LED	∅ 5X36PCS
Infrared Distance	30M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control

NETWORK

Ethernet Protocol	RJ-45 (10/100Base-T) IPv4, HTTP, TCPIP, FTP, NTP, RTSP, UDP, SMTP, DNS, DDNS
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Yes (Optional)
Video Delay	0.3S (Within the Lan)
Main Stream	1280*960 30fps
Sub Stream	704*576@30fps
IE Brower	IE6-11, Google Chrome (IE Tab), Firefox(IE Tab)
Smart Phone	iPhone, iPad, Android, Android Tablet

GENERAL

Housing	Metal
Anti-cut Bracket	Yes , 3-Axis
IR Cut Filter	YES
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 700mA
Dimension	∅ 135 x 110(H) mm
Weight	2kg

Visit us at : www.mountxross.com
 For Enquiry : info@mountxross.com
 For Sales : sales@mountxross.com
 Contact us : +8613510224602

Distributor